

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

WATER ABSORBING RESIN COMPOSITION

Patent Number: JP58183754
 Publication date: 1983-10-27
 Inventor(s): TANAKA KENJI; others: 03
 Applicant(s): SANYO KASEI KOGYO KK
 Requested Patent: ☐ JP58183754
 Application Number: JP19820066133 19820420
 Priority Number(s):
 IPC Classification: C08L101/00 ; A41B13/02 ; A61F13/00 ; C08K5/05
 EC Classification:
 Equivalents: JP1696522C, JP3062745B

Abstract

PURPOSE: A resin composition, prepared by incorporating a powdery water-insoluble and water absorbing resin with a specific amount of a polyhydric alcohol, and capable of promoting the uniform permeation of water and exhibiting a remarkably high water absorption rate.

CONSTITUTION: A water absorbing resin composition prepared by incorporating (A) a powdery water-insoluble and water absorbing resin, e.g. a water-insoluble hydrophilic crosslinked polymer obtained by polymerizing a water-soluble monomer and/or a monomer made soluble in water by the hydrolysis, a polysaccharide and a crosslinking agent, and if necessary hydrolyzing the resultant polymer with (B) 0.001-5wt%, preferably 0.01-2wt%, based on the component (A), bi-octavalent polyhydric alcohol and/or oxyalkylene ether thereof, preferably bi-trivalent for the former and bi-tetravalent for the latter. Ethylene glycol, propylene glycol, glycerol and an ethylene oxide (EO) or propylene oxide (PO) adduct thereof having $\leq 2,000$ cP viscosity at 25 deg. C is preferably used as the component (B).

Data supplied from the esp@cenet database - 12